



0955 284 201/... M beidseitig / both sides

0955 284 202/... M einseitig - Stecker / one side - male

0955 284 203/... M einseitig - Kupplung / one side - female

Interbus Fernbuskabel
beidseitig konfektioniert:
 mit M23-Stecker und M23-
 Kupplung, 9-polig
einseitig konfektioniert:
 mit M23-Stecker oder M23-
 Kupplung, 9-polig

Interbus remote bus cable
assembled on both sides:
 with M23 male connector and
 M23 female connector, 9 poles
assembled on one side:
 with M23 male connector or
 M23 female connector, 9 poles

0955 284 204/... M beidseitig / both sides

Interbus Fernbuskabel
beidseitig konfektioniert:
 mit M23-Kupplung und SUBD-
 Stecker, 9-polig

Interbus remote bus cable
assembled on both sides:
 with M23 female connector
 and SUBD male connector,
 9 poles

M23-Kupplung / SUBD-Stecker, 9-polig M23 female connector / SUBD male connector, 9 poles	Signal Signal	Farbe Color
Pin 1	DO	gelb / yellow
Pin 2	DO	grün / green
Pin 3	DI	grau / grey
Pin 4	DI	rosa / pink
Pin 5	COM	braun / brown
Pin 6	n.c.	
Pin 7	n.c.	
Pin 8	n.c.	
Pin 9	RBST	
Gehäuse / housing	Schirm / shield	Schirmgeflecht / shield braiding

1) = nur im SUBD-Stecker / only in SUBD male connector

**Bestellbezeichnung
Designation**

0955 284 201/... M	 
0955 284 202/... M	 
0955 284 203/... M	 
0955 284 204/... M	 

Standardlängen: 0955 284 201/... M: 0,3 M / 0,6 M / 1 M / 2 M / 3 M / 5 M / 10 M / 15 M / 20 M / 25 M
 0955 284 202/... M / 0955 284 203/... M: 1 M / 3 M / 5 M / 10 M / 15 M
 0955 284 204/... M: 1 M / 2 M / 3 M / 5 M
 Andere Kabellängen oder Leitungsaufbauten auf Anfrage.

Standard lengths: 0955 284 201/... M: 0.3 M / 0.6 M / 1 M / 2 M / 3 M / 5 M / 10 M / 15 M / 20 M / 25 M
 0955 284 202/... M / 0955 284 203/... M: 1 M / 3 M / 5 M / 10 M / 15 M
 0955 284 204/... M: 1 M / 2 M / 3 M / 5 M
 Other cable lengths or cable specifications on request.