


**0935 253 101/... M**

beidseitig / both sides

CAN-/DeviceNet-Thin Cable  
**beidseitig umspritzt:**  
 mit 7/8"-Stecker und  
 M12-Kupplung, 5-polig

CAN/DeviceNet Thin Cable  
**molded on both sides:**  
 with 7/8" male connector and  
 M12 female connector, 5 poles

**0935 253 102/... M**

beidseitig / both sides

CAN-/DeviceNet-Thin Cable  
**beidseitig umspritzt:**  
 mit M12-Stecker und 7/8"-  
 Kupplung, 5-polig

CAN/DeviceNet Thin Cable  
**molded on both sides:**  
 with M12 male connector and  
 7/8" female connector, 5 poles

Stecker / Kupplung, 5-polig male connector / female connector, 5 poles	Funktion Function	Farbe Color
Pin 1	Schirm / shield	
Pin 2	+ 24 V	rot / red
Pin 3	GND (0 V)	schwarz / black
Pin 4	CAN_H	weiß / white
Pin 5	CAN_L	blau / blue

**Bestellbezeichnung  
Designation**

0935 253 101/... M



0935 253 102/... M



Standardlängen: 1 M / 2 M / 3 M / 5 M  
 Andere Kabellängen oder Leitungsaufbauten auf Anfrage.

Standard lengths: 1 M / 2 M / 3 M / 5 M  
 Other cable lengths or cable specifications on request.