

220, 221, 222 Series Beacons

Technical specifications

Housing:	PA fibreglass, high-impact
Dome:	PC, transparent Ring: PC/ABS-Blend
Connection:	CAGE CLAMP® technology max. 2,5 mm ² Contacts protection according to VDE
Cable entry:	Cable diameter max. 10 mm (220 - 222) Cable gland M12 x 1.5 Cable diameter 3 - 6 mm (223 - 225)

Permanent Light	220
------------------------	------------

Fixing:	Base mounting with flat seal
Dimensions(Diameter x Height):	75 mm x 80 mm
Weight:	97 g
Operating voltage:	max. 250 V
Bulb socket:	B 15d, 10 Watt max.
Bulb change:	via removal of dome
Bulbs not included in assembly	

LED-permanent	221
----------------------	------------

Fixing:	Base mounting with flat seal
Dimensions(Diameter x Height):	75 mm x 80 mm
Weight:	108 g
Operating voltage:	24 V =-, 115 V~, 230 V~
Current consumption:	45 mA at 24 V 25 mA at 115 V 25 mA at 230 V
Starting current:	< 0,5 A at 24 V

Flashing light	222
-----------------------	------------

Fixing:	Base mounting with flat seal
Dimensions (Diameter x Height):	75 mm x 80 mm
Weight:	124 g
Flash frequency:	ca. 0,75 Hz
Life duration:	4 x 10 ⁶ flashes
Operating voltage:	24 V =, 115 V~, 230 V~
Current consumption:	100 mA at 24 V 20 mA at 115 V 30 mA at 230 V

